

7

8

1

3 0 1

∭ 1 ∭ 2

₩ 5

6

7

8

9

10

11

12

13

CLAIMS

- A method for arranging a plurality of orders for printed articles each of which
 contains one or more printed articles, in order to reduce wasted space when printing the
 orders in multiple columns, the method comprising the steps of:
 obtaining a plurality of orders for at least one printed article;
 sorting the orders according to the number of printed articles in each order to
 produce a sorted arrangement of the orders; and
 - for each successive order in the sorted arrangement of orders placing the order in a column which currently has a lowest number of total printed articles.
 - The method of claim 1 further comprising the step of:
 placing the first K orders in the sorted arrangement of orders in columns 1 to K
 where K is the total number of columns.
 - 3. The method of claim 1 further comprising the steps of:
 determining the number of printed articles in a lth group in an Mth column;
 determining the number of printed articles in the Mth column;
 determining the number of printed articles in a Jth group in a Nth column;
 determining a number of printed articles in the Nth column; and
 exchanging the lth and Jth groups between the Mth and Nth columns if:
 (L(M)>L(N) AND L(I,M)>L(J,N) AND L(M)-L(N)>L(I,M)-L(J,N)) OR
 (L(M)<L(N) AND L(I,M)<L(J,N) AND L(N)-L(M)>L(J,N)-L(I,M))
 where L(M) is the number of printed articles in the Mth column,
 L(I,M) is the number of printed articles in the Ith order of the Mth column, and
 L(J,N) is the number of printed articles in the Jth order of the Nth column

is true.

EXPRESS MAIL NO.: EL563155095US

- 4. A method for rearranging a data structure representing a multi column
 arrangement of a plurality of groups of printed matter the method comprising the steps
 of:
- 4 determining the number of printed articles in a lth group in a Mth column;
- determining the number of printed articles in the Mth column;
- 6 determining the number of printed articles in a Jth group in a Nth column;
- determining a number of printed articles in the Nth column; and
- 8 exchanging the Ith and Jth groups between the Mth and Nth columns if:
- 9 (L(M)>L(N) AND L(I,M)>L(J,N) AND L(M)-L(N)>L(I,M)-L(J,N)) OR
- 10 (L(M)<L(N) AND L(I,M)<L(J,N) AND L(N)-L(M)>L(J,N)-L(I,M))
- where L(M) is the number of printed articles in the Mth column,
- 12 L(N) is the number of printed articles in the Nth column,
- L(I,M) is the number of printed articles in the Ith order of the Mth column, and
 - L(J,N) is the number of printed articles in the Jth order of the Nth column
 - is true.


ľIJ

2

- The method of claim 4 further comprising the step of iteratively selecting different combinations values of M and N.
- 6. The method of claim 4 further comprising the step of:
- iteratively selecting different combinations of values of I and J.

EXPRESS MAIL NO.: EL563155095US

7	7. A computer readable medium containing programming instructions	tor
2	rearranging a data structure representing a multi column arrangement of a	a plurality of
3	groups of printed matter, including programming instructions for	
4	determining the number of printed articles in a Ith group in a Mth co	olumn;
5	determining the number of printed articles in the Mth column;	
6	determining the number of printed articles in a Jth group in a Nth co	olumn;
7	determining a number of printed articles in the Nth column; and	
8	exchanging the Ith and Jth groups between the Mth and Nth colum	ns if:
9	(L(M)>L(N) AND L(I,M)>L(J,N) AND L(M)-L(N)>L(I,M)-L(J,N)) OR	
0	(L(M) < L(N) AND L(I,M) < L(J,N) AND L(N) - L(M) > L(J,N) - L(I,M))	
1	where L(M) is the number of printed articles in the Mth column,	
2	L(N) is the number of printed articles in the Nth column,	
3	L(I,M) is the number of printed articles in the Ith order of the Mth co	lumn, and
4	L(J,N) is the number of printed articles in the Jth order of the Nth co	olumn
5	is true.	



1	8. A computer readable medium containing programming instructions for	
2	rearranging a data structure representing a multi column arrangement of a plurality of	
3	groups of printed matter the computer readable medium including programming	
4	instructions for:	
5	determining the number of printed articles in a Ith group in a Mth column;	
6	determining the number of printed articles in the Mth column;	
7	determining the number of printed articles in a Jth group in a Nth column;	
8	determining a number of printed articles in the Nth column; and	
9	exchanging the Ith and Jth groups between the Mth and Nth columns if a	
10	boolean expression:	
11	(L(M)>L(N) AND L(I,M)>L(J,N) AND L(M)-L(N)>L(I,M)-L(J,N)) OR	
12	(L(M) < L(N) AND L(I,M) < L(J,N) AND L(N)-L(M) > L(J,N)-L(I,M))	
13	where L(M) is the number of printed articles in the Mth column,	
14 15	L(N) is the number of printed articles in the Nth column,	
<u></u>	L(I,M) is the number of printed articles in the Ith order of the Mth column, and	
116	L(J,N) is the number of printed articles in the Jth order of the Nth column	
	is true	



EXPRESS MAIL NO.: EL563155095US

7	9.	9. A system for producing custom printed articles comprising.	
2	a high speed printer;		
3	a server electrically coupled to the high speed printer the server including:		
4		a processor programmed to:	
5		determine a number of printed articles in a Ith group in a Mth column;	
6		determine a number of printed articles in the Mth column;	
7		determine a number of printed articles in a Jth group in a Nth column;	
8		determine a number of printed articles in the Nth column; and	
9		exchange the Ith and Jth groups between the Mth and Nth columns if a	
10	boolean expression:		
11		(L(M)>L(N) AND L(I,M)>L(J,N) AND L(M)-L(N)>L(I,M)-L(J,N)) OR	
12		(L(M) < L(N) AND L(I,M) < L(J,N) AND L(N) - L(M) > L(J,N) - L(I,M))	
13		where L(M) is the number of printed articles in the Mth column,	
14		L(N) is the number of printed articles in the Nth column,	
15		L(I,M) is the number of printed articles in the Ith order of the Mth column	
16	and		
17		L(J,N) is the number of printed articles in the Jth order of the Nth column	
18		is true.	